

DUO PRO-PESTREPELLER®

DUO PRO-PESTREPELLER consists of two efficient high frequency generators, transducer and dual speakers, to drive rodents and insects away electronically and intensively! The device is suitable for using in home, apartment, restaurant, school, office, basement or any indoor areas.

DUO PRO-PESTREPELLER is effective in controlling mice, rats, roaches, fleas, crickets, ants and most of the other common pests. Laboratory research has shown ultrasonic sound waves attack the auditory and nervous systems of most common pests causing them pain and discomfort. With up to 135 decibels of sound pressure, pests will give up their source of food, water and shelter and move on. These high-intensity sound waves are out of the range of hearing of human beings and most household pets.

DUO PRO-PESTREPELLER will not interfere with televisions, radios, electronic burglar alarms, fire or smoke detectors, pacemakers, hearing aids or other electronic equipment. **DUO PRO-PESTREPELLER** will not harm plants, either.

CHARACTER

DUO PRO-PESTREPELLER is a device can emit auto-changed and auto-sweeping high intensity frequency range of 25,000Hz – 65,000Hz from its dual speakers and/or frequency of 25,000Hz from transducer. The unique DUO circuit design strikes the auditory and nervous systems of the pests strongly with its intensive and wide range of ultrasonic waves. This function is effective to drive pests away from the protection area speedily and to prevent pests from immunity to a pre-selected single sweeping rate.

DUO PRO-PESTREPELLER is the grand pest control device of its kind. It effectively protects an area measuring 5,000 – 6000 unobstructed square feet or 468 – 545 unobstructed square meters. **DUO PRO-PESTREPELLER** is equipped with a switch of four modes, DUO, TRANS, ULTRA, TEST. After plugging **DUO PRO-PESTREPELLER** in, you will be able to select the mode according to your actual requirement.

DUO: Intermittent impulse attack waves plus frequency sweeping attack waves will be projected from both of the dual speakers and the transducer. The beat frequency produced during the DUO mode is normal operation.

TRANS: Intermittent impulse attack waves will be projected from the transducer system.

ULTRA: Frequency sweeping attack waves will be projected from the dual speaker system.

TEST: The device will shift its output down into the audible range of human beings for a reassuring check of its ultrasonic output when switch to the TEST mode. The shrill, shock, unregulated siren-like sound produced simulates the sound that pests hear continually.

USAGE

Just plug in electricity **DUO PRO-PESTREPELLER** can be used indoors at any time. You will begin to notice the

effects of **DUO PRO-PESTREPELLER** in a few days. There will be an absence of rodent activity. Perhaps you will notice an increase in insect's activity during this time due to the ultrasonic sound waves driving these pests from hiding. In a short while they'll be gone also. While the pests are being driven away, they are undoubtedly leaving their eggs and larvae behind which are not affected by the ultrasonic sound waves. Incubation will continue and they'll hatch as usual. However, **DUO PRO-PESTREPELLER's** ultrasonic output will begin to attack their auditory and nervous systems, driving this new generation away. In 3 to 5 weeks the infestation should be over and you'll be free of pests. Leave **DUO PRO-PESTREPELLER** plugged in for year round, day and night pest control. It costs only about 1½¢ a day to operate. No more dangerous chemicals to buy, no more messy traps to clean.

NOTICE

Do not place **DUO PRO-PESTREPELLER** on carpeted surfaces, behind furniture, draperies or other soft objects as they will absorb the sound waves.


Do not place **DUO PRO-PESTREPELLER** next to your ear before performing the check by switching to TEST mode on the back panel.

Do not use **DUO PRO-PESTREPELLER** outdoors or let the unit come in contact with water.


SPECIFICATIONS

Dimensions:	119 x 98 x 98 mm
Weight:	180g
Power supply:	AC adaptor: 100-120 VAC, 60 cycles 220-240 VAC, 50 cycles
	Output: 9VDC 200mA
Power consumption:	1½ watts
Frequency range:	25,000Hz to 65,000Hz (continuously variable)
Output sound pressure:	135 dB (decibel)
Emission angle:	260°

HOW ULTRASOUND WAVES REFLECT:



SWITCH MODE: ■ DUO
■ TRANS
■ ULTRA
■ TEST



DC 9V INPUT

LED INDICATOR: GREEN: TRANS MODE
RED: ULTRA MODE

TRANSDUCER

ULTRASONIC EMISSION SPEAKERS

